




ANSI SPROCKET



100

NOTE

mm

Pitch

31.75

Roller Φ

19.05

h

17.58

h1

16.99

h2

52.76

Dimensions: mm

Teeth	OD	P.C.D	Bore:d	Type B Simplex			Type B Duplex				Material
				Hub		Weight kg	Bore:d	Hub		Weight kg	
				BD	BL			BD	BL		
8	95.8	83.0	25.4	61.9	47.63	1.04					C45
9	106.2	92.8	25.4	71.4	47.63	1.44	25.40	60.33	73.03	2.07	
10	116.8	102.7	25.4	82.6	47.63	1.85	25.40	69.85	73.03	2.79	
11	127.3	112.7	25.4	90.5	47.63	2.39	25.40	79.38	73.03	3.56	
12	137.7	122.7	25.4	101.6	47.63	2.88	28.58	85.73	73.03	4.19	
13	147.8	132.7	25.4	98.4	41.28	2.97	28.58	96.84	73.03	5.13	
14	158.2	168.1	31.75	106.4	41.28	3.33	28.58	106.36	73.03	6.12	
15	168.4	152.7	31.75	114.3	44.45	4.14	31.75	117.48	79.38	7.70	
16	178.6	162.8	33.34	114.3	44.45	4.46	31.75	127.00	79.38	9.05	
17	189.0	172.8	33.34	114.3	44.45	4.86	31.75	133.35	79.38	10.40	
18	199.1	182.9	33.34	114.3	44.45	5.18	31.75	133.35	79.38	11.43	
19	209.3	192.9	33.34	114.3	50.80	5.90	31.75	139.70	85.73	13.32	
20	219.5	202.9	33.34	114.3	50.80	6.39	31.75	139.70	85.73	14.58	
21	229.6	213.1	33.34	114.3	50.80	6.89	31.75	139.70	85.73	15.89	
22	239.8	223.1	33.34	114.3	50.80	7.25	31.75	139.70	85.73	17.28	
23	249.9	233.2	31.75	114.3	50.80	7.74	31.75	139.70	85.73	18.59	
24	260.4	243.2	31.75	114.3	50.80	8.64	31.75	146.05	85.73	20.30	
25	270.5	253.3	31.75	114.3	50.80	8.78	31.75	146.05	85.73	21.83	
26	280.7	263.4	31.75	127.0	50.80	9.77	38.10	146.05	85.73	23.18	
27	290.6	273.5	31.75	127.0	50.80	10.35					
28	300.7	283.6	31.75	127.0	50.80	10.98					
29	310.9	293.6	31.75	127.0	50.80	11.25					
30	321.1	303.8	31.75	127.0	50.80	12.11	38.10	146.05	85.73	29.25	
31	340.4	313.8	31.75	127.0	50.80	12.69					
32	341.4	323.9	31.75	127.0	50.80	13.41					
33	351.5	334.0	31.75	127.0	50.80	14.45					
34	361.7	344.1	31.75	127.0	63.50	15.53					
35	371.9	354.2	31.75	127.0	63.50	16.61	38.10	152.40	107.95	33.75	
36	382.0	364.3	31.75	127.0	63.50	17.37					
37	392.2	374.4	31.75	127.0	63.50	18.00					
38	402.3	384.5	31.75	127.0	63.50	18.68					
39	412.2	394.6	31.75	127.0	63.50	19.62					
40	422.4	404.7	31.75	127.0	63.50	21.11					
41	432.6	414.8	31.75	127.0	63.50	21.87					
42	442.7	424.9	31.75	127.0	63.50	22.68					
43	452.9	435.0	38.10	127.0	63.50	23.22					
44	463.0	445.1	38.10	127.0	63.50	23.76					
45	473.2	455.2	38.10	127.0	63.50	24.30	38.10	152.40	114.30	46.35	
46	483.1	465.3	38.10	127.0	63.50	25.20					
47	493.3	475.4	38.10	127.0	63.50	26.19					
48	503.4	485.5	38.10	127.0	63.50	27.45					
60							38.10	190.50	127.00	78.75	
70							38.10	190.50	127.00	88.65	
80							38.10	190.50	127.00	103.95	